

Reading codes off mobile phone screens

	Datalogic						Honeywell				
	Gryphon™ GBT4400 2D	PowerScan™ PD 9500	PowerScan™ PM9500	QuickScan™ QD2400	QuickScan QM2400	QuickScan™ Lite QW2100	Genesis 7580g	Intermec SF61B	Voyager 1400G	Voyager 1602g	Xenon 1900
											
Decoding	1D/Linear / 2D / Postal / Stacked	1D/Linear / 2D / Postal / Stacked	1D/Linear / 2D / Postal / Stacked	1D/Linear / 2D / Postal / Stacked	1D / 2D / Postal / Stacked	1D / Linear / Postal / Stacked	1D, PDF, 2D, Postal and OCR	2D / Linear	2D / Linear	1D / 2D	1D, PDF, 2D, Postal and OCR
Interface	RS-232/IBM 46XX/ USB Multi-Interface; RS-232 /USB Kboard Wedge/Wand Multi-Interface	RS-232 / USB / Keyboard Wedge Multi-Interface	Keyboard Wedge; RS-232; RS-485; USB; OEM USB; USB COM; USB HID Keyboard	Keyboard Wedge / OEM (IBM) USB / RS-232 / USB	Keyboard Wedge / OEM (IBM) USB / RS-232 / USB	QW2170-BK: RS-232 / Keyboard Wedge QW2120-BK: USB	USB, RS232, Keyboard Wedge, IBM 46xx (RS485)	USB, OS compatibility: Apple iOS®; Google Android®; Microsoft Windows® XP, Vista, 7, 8	USB, Keyboard Wedge, RS232, IBM 46xx (RS485)	Wireless Area imager	USB, Keyboard Wedge, RS232, IBM 46xx (RS485)
Drop resistance	5.9 ft	6.6 ft	3.9 ft	5 ft	4.9 ft	5ft	5ft	6.5 ft	5ft	4ft	6ft
Water sealing	IP52	IP65	IP65	IP42	IP42	IP42	0% to 95% relative humidity	IP65	IP42	IP42	IP41
Tethered	Cordless	Corded	Cordless	Corded	Cordless	Corded	Corded	Cordless	Corded	Cordless	Corded
Reading distance*	0.5 to 30cm	Omnidirectional from contact to over 1.0 m / 3.3 ft	2 to 110cm (PM9500-HP)	0.5 to 15.0 cm	0.5 to 16.0 cm	Contact to 60cm	Contact to 190mm	0.1 to 117cm	Up to 10 cm	32 to 408 mm	Up to 610 cm/s
Operating temp	0 to 50 °C	-20 to 50 °C	-20 to 50 °C	0 to 50 °C	0 to 50 °C	0 to 50 °C	0 to 40 °C	-20°C to +50°C	0 to 40 °C	0 to 50 °C	0 to 50 °C
Power	Li-Ion, 2100 mAh	PD9530/PD9530-HP: 5 VDC +/- 10% PD9530-HPE: 10-30VDC	Li-Ion 2150 mAh	140 mA @ 5 VDC	Li-Ion 1400 mAh	340 mA @ 5 VDC	5.5 VDC ± 0.25 V 400 mA @ 5 V	Li-Ion 2,600 mAh	400mA @ 5 VDC 4.0 to 5.5 VDC	750 mAh Li-ion	450mA @ 5 VDC 4.0 to 5.5 VDC
Dimensions	Cradle: 18.6 x 9.9 x 5.6 cm. Reader: 18.1 x 7.1 x 10.0 cm	212 x 110 x 74 mm	212 x 110 x 74 mm	163 x 91 x 41 mm	163 x 91 x 41 mm	170 x 65 x 70 mm	80 x 83 x 150 mm	156 x 46 x 39mm	100 x 66 x 43mm	120 x 48 x 22 mm	104 x 71 x 160mm
Weight	Cradle: 246g. Reader: 245g	330 g	PM9500: 380g PM9500/D: 400g	145g	200g Base 230g	119g	340g	184g	119g	< 100 g	147g
Warranty	3 years	3 years	3 years	5 years	3 years	3 years	3 years	3 years	5 years	3 years	5 years
Notes	Bluetooth Class 2		433mhz and BT option available		433mhz		Remote MasterMind™ Scanner Management Software	Bluetooth Class 1 v2.1+EDR		Bluetooth v2.1; Class 2	

* Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

Reading codes off mobile phone screens

Zebra				
	LI 4278	DS4308	DS4800	DS6878
				
Decoding	1D, UPC	1D / 2D / Postal	1D / 2D / Postal	1D / 2D / Postal / PDF417
Interface	RS232, RS485 (IBM), USB, Keyboard Wedge	USB, RS232, Keyboard Wedge, RS485 (IBM 46xx), SS I	USB	RS-232C, USB, Keyboard Wedge, Synapse
Drop resistance	6ft	6ft	5ft	6ft
Water sealing	Gasket sealed housing	5% to 95%, non-condensing	IP40	5% to 95%, non-condensing
Tethered	Cordless	Corded	Corded	Cordless
Reading distance*	3.8-48.3 cm	0 to 41.1cm	0 to 444.5cm	1.2 to 18.3cm
Operating temp	0° C to 50° C	0 to 50 °C	0 to 40 °C	0 to 50 °C
Power	Rechargeable replaceable	5 VDC ± 10% @ 360 mA	5VDC +- 10% @ 360 mA	5 +/-10% VDC 700 mA/260 mA
Dimensions	98 x 7 x 186 mm	165 x 98 x 67mm	190 x 66 x 48mm	185 x 97 x 69mm
Weight	224 g	162g	168g	238g. Base 183g
Warranty	3 years	5 years	5 years	3 years
Notes	BT v2.1 Class 2. Compatible with 123Scan and RSM			BT Class 1, Version 2.1 + EDR
<i>* Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.</i>				