

	CIPHERLAB					DATALOGIC					
	1166/1266	1560/1564	1560	1660	1664	Gryphon	PowerScan PBT9100	Powerscan PBT9300	Powerscan PM9300	Powerscan PD9x00 range	Quickscan QM2131
											
<b>Scan Engine</b>	Linear Imager / Laser	Linear Imager / Area Imager	Linear	Linear	Linear	Laser / Linear Imager / Area Imager	Laser / Linear Imager	Laser	Laser	Laser / Area Imager / HP Area Imager	Linear / Stacked
<b>1D/2D</b>	1D	1D/2D	1D/2D	1D/2D	2D	1D/2D	1D/2D	1D/2D	1D/2D	1D/2D	1D
<b>Interface</b>	USB/KBW/RS32/Bluetooth C2 V2	USB/KBW/RS32/Bluetooth C2 V2	Bluetooth	Bluetooth / USB	Bluetooth / USB	USB/KBW/RS232/WAND	Keyboard Wedge RS-232; USB: OEM USB; USB COM; USB HID Keyboard; Optional Ethernet	KBW; RS-232; USB: Keyboard; Opt Ethernet	KBW; RS-232; USB: Keyboard; Opt Ethernet	USB/KBW/RS232/ WAND	Keyboard Wedge / OEM (IBM) USB / RS-232 / USB
<b>Rugged</b>	No	No				No	Yes	Yes	Yes	Yes	
<b>Operating temp (°C)</b>	0-50	0-50	0-50	0-50	0-50	0-50	-20 to 50 °	-20 to 50 °	-20 to 50 °	-20 to 50	0 to 50 °C
<b>Tethered</b>	Cordless	Cordless	Cordless	Cordless	Cordless	Corded / Cordless	Cordless	Cordless	Cordless	Corded / Cordless	Cordless
<b>Reading distance</b>	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard / Auto Range / Long Range	2.0 to 45.0 cm
<b>Warranty</b>	3 year / 1 year	3 year	5 years	1 year	1 year	3 / 5 years	3 years	3 years	3 years	3 / 5 years	3 years
<b>Price bracket</b>	Medium	Medium	Medium	Low	Low	Medium				High	

	Honeywell					Intermec	Opticon						
	Granit 1911i	Granit 1981i	Voyager 1452g	Voyager 1602g Pocket scanner	Xenon 1902g	SR61B	OPC-3301i	OPH-1005 Batch Terminal – Handheld mobile computer	OPN-2001 Pocket memory scanner	OPN-2006 Companion scanner	OPN-3002i Companion scanner	PX-20 Companion scanner	OPN-4000i Companion scanner
													
<b>Scan Engine</b>	Area Imager	Area Imager	Area Imager	Area Imager	Area Imager	Area Imager	Barcode CCD	Laser barcode scanner					CCD linear sensor
<b>1D/2D</b>	1D/2D	1D/2	1D/2D	1D/2D	1D/2D	1D/2D	1D / POSTAL	1D / 2D / POSTAL	1D / POSTAL	1D / POSTAL	1D / 2D / POSTAL	1D / 2D / POSTAL	1D / POSTAL
<b>Interface</b>	USB/KBW/RS32 TTL	Wireless	USB, Keyboard Wedge, RS232 TTL, IBM 46xx (RS485)	integrated Bluetooth® Class 2	USB/KBW/RS32/IBM/BT C2 V2.1	USB/KBW/RS32/Wand/Bluetooth C1 V1.2	Bluetooth	IRDA: Version 1.2	USB	USB and Bluetooth v3.0 Programmable	USB and Bluetooth v2.1 Programmable	USB and Bluetooth v2.1 Programmable	USB and Bluetooth v2.1
<b>Rugged</b>	Yes	Yes	Yes	Yes	No	Yes	No	Yes	N/A	N/A	N/A	N/A	Yes
<b>Operating temp (°C)</b>	-20 to 50	-20°C TO 50°	5°C TO 40°C	0-50	0-50	-20 to 50	0-50	-10 to 50	0-40	0-40	0-50	-10 to 50	0-50
<b>Tethered</b>	Cordless	Cordless	Cordless	Cordless	Cordless	Cordless	Cordless	Battery Li-Ion 3.7V	Cordless. Battery Li-Ion 3.7V	Cordless. iOS and Android compatible	Cordless. iOS and Android compatible	Cordless. iOS and Android compatible	Cordless. iOS, Android and Windows compatible
<b>Reading distance</b>	Extended	Extended	Standard	Standard	Standard	Standard / Auto	Standard						
<b>Warranty</b>	3 year	3 year	3 years	3 year	3 year	3 year	2 years	2 years	2 years	2 years	2 years	2 years	2 years
<b>Price bracket</b>	High	High			High	High	Medium						

	Unitech	Zebra											
	MS352	CS3000	DS2278	DS6878	DS2278	DS3500	3600 SERIES ULTRA RUGGED	LI4278	SS4070-HC (Healthcare)	PS20 Personal shopper (Android)	CS4070	DS4308	CS4700
													
<b>Scan Engine</b>	Bluetooth Scanner	Laser	Area Imager	Area Imager	Linear Imager	Area Imager		Linear Imager	SE4710 image	Base model: SE2100 1D/2D imager Plus model: SE4710 1D/2D imager + Digimarc support	SE4710 image engine	2D imager	SE4710 image engine
<b>1D/2D</b>	1D/2D	1D	1D/2D	1D/2D	1D/2D	1D/2D	1D	1D	1D/2D	1D/2D	1D/2D	1D/2D/Postal	1D/2D
<b>Interface</b>	Bluetooth 4.0, Class 2 Range	USB	USB/KBW/RS32/TGCS (IBM) over RS485	USB/KBW/RS232/IBM/WAND/BT V2.1 C1	USB/KBW/RS32/TGCS (IBM) over RS485	USB/KBW/RS232/BT C2 0V2.1	USB, RS232, Keyboard Wedge	BT V2.1 +EDR	USB (micro jack): Bluetooth	USB 2.0	USB (micro jack): Bluetooth	USB/KBW/RS232/RS485 (IBM 46XX), SSI	USB (micro jack): Bluetooth
<b>Rugged</b>	Drop Sec: 1.5. IP51	No	Multiple 1.5m drops to concrete	No	No	Yes	Ultra	Yes	Yes	Yes	Yes	Yes	Yes
<b>Operating temp (°C)</b>	0-50	0-40	0-50	0-55	0-50	-20 to 50	-20 to 50	0-50	0-40	10 to 50	0° to 40° C	0° to 50° C	0° to 40° C
<b>Tethered</b>	Cradle thered, Scanner cordless	Cordless	Cordless	Cordless	Corded or DS2278 cordless	Corded / Cordless	LI3678-ER (cordless) and LI3608-ER and LI3678-ER (corded)	Cordless	Cordless	Cordless	Cordless	Power supplies are available for applications that do not supply power over the host cable	Cordless
<b>Reading distance</b>	Standard	Standard	110,000 scans at 60 scans per minute or 50,000 scans at 10 scans per minute	Standard	123 - 368 mm	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
<b>Warranty</b>	4 year limited	1 year	5 year	3 year	5 year	3 year	3 years	3 year	3 year		3 year	3 year	3 years
<b>Price bracket</b>		Low		Medium		High		Low - Mid					

For further information contact us at: **t:** 01928 718800 **email:** [helen.jones@spiritdatacapture.co.uk](mailto:helen.jones@spiritdatacapture.co.uk) **www:** [www.spiritdatacapture.co.uk](http://www.spiritdatacapture.co.uk)

Whilst every effort has been made to verify the accuracy of the data, Spirit Data Capture is not liable for any errors, loss or damage arising in any way from receipt or use thereof. *Last Updated September 2018.*